

JVA Cellular Gateway

PTE0320

Overview:

The JVA Cellular Gateway allows easy remote control and monitoring of Z-Series Energisers and Monitors by your mobile phone or computer, through JVA's Cloud Router® system. It also includes extra inputs and outputs to interface with other security equipment or ancillary equipment such as an electric gate motor. For more information on the Cloud Router® system, visit <http://jva-fence.com/security/cloudrouter> or contact JVA.

Features:

- Compatible with all JVA Z series energisers, monitors and other devices
- Monitors and controls up to 15 devices (linked via Keypad bus) as well as two inputs and two output relays
- 4G variant available, with frequencies to suit all countries
- No configuration required
- Takes a standard micro-SIM or nano-SIM (4G)
- Very low data usage means SIM credit lasts up to a year
- Additional SMS-based control and monitoring
- Can be used in conjunction with Perimeter Patrol

Specifications:

Network	PTE0320 (2G): PTE0320-3G: PTE0320-4G:	850/900/1800/1900 B1/2/5/6/8/19 + 2G B1/3/5/7/28, 3G B1/5
Interfaces to	Energisers: Monitors:	Z14R, Z28, etc ZM1, ZM20, ZLM4, etc
Power Supply	External or by Keypad Bus:	12V DC 200mA
Connections	Inputs: Outputs:	2 x dry contact 2 x 30Vdc 8A SPDT
Size	Height: Width: Depth:	135 mm 128 mm 40 mm
Weight	Product:	200 g



Warranty:

3 Year Manufacturer Warranty (excluding lightning damage)

For more information:

See the Setup Guide at: <http://jva-fence.com/CloudRouterGuide.html>

